

PRODUCT NAME

Graffiti Shield ST WB Cleaner

Graffiti Cleaner

MANUFACTURER

Gemite® Products Inc.

Toll Free: 888-4-GEMITE (888-443-6483)

E-mail: techinfo@gemite.com

Web Site: www.gemite.com

USA

160-3480 East Robinson Rd.

Amherst, NY 14228

Phone 888-443-6483

Fax 888-443-6329

CANADA

1787 Drew Road

Mississauga, Ontario L5S 1J5

Phone 905-672-2020

Fax 905-672-6780

FEATURES

- Easy to use
- Highly active
- Non-regulated for transportation
- Economical
- Spray, roller or brush applied

PRODUCT DESCRIPTION

Basic Use

It is used in removal of graffiti from *Graffiti-Shield ST WB* protective coating applied to wall surfaces.

Composition and Materials

Graffiti-Shield ST WB Cleaner is in oil emulsified organic cleaner used to remove graffiti. After approximately 30-40 cleanings, the film of the *Graffiti-Shield ST WB* is diminished and the surface needs to be re-coated with *Graffiti-Shield ST WB*.

Limitations

Do not apply *Graffiti-Shield ST WB Cleaner* when air temperature or surface temperature are or likely to be lower than 41°F (5°C) or when rain is imminent. Some graffiti may remain on rough surfaces, even after the cleaning.

Health and Safety

Graffiti-Shield ST WB Cleaner is non-hazardous and non-regulated. If contact with skin occurs, wash with water & soap. Harmful if digested. Keep the products out of reach of children. FOR INDUSTRIAL USE ONLY. Consult SDS for additional information.

Packaging

Graffiti-Shield ST WB Cleaner is sold in 20 L (5.3 USG) pails.



Coverage

Yield of *Graffiti-Shield ST WB Cleaner* will vary considerably with the type and age of the graffiti, and surface roughness.

Storage and Transportation

Graffiti-Shield ST WB Cleaner has a shelf-life of 12 months when stored in unopened containers on pallets in a cool dry area.

GRAFFITI REMOVAL

Current Guide Specifications and Application instructions contain information specific to each application and must be followed.

To remove graffiti from *Graffiti-Shield ST WB* treated substrates apply *Graffiti-Shield ST WB Cleaner* by spraying, rolling or brushing.

Spraying is preferable, particularly on rough surfaces.

Let the *Graffiti-Shield ST WB Cleaner* act on the graffiti for 10-15 minutes and then wash with 2,000-2,500 psi (14-17 MPa) pressure water.

On rough surfaces that may “lock-in” the graffiti, or some graffiti sprays, the removal may not be complete and the procedure may have to be repeated.

After approximately 30-40 graffiti removals the surface will require re-application of *Graffiti-Shield ST WB*.

AVAILABILITY AND COST

Graffiti-Shield ST WB Cleaner is available worldwide. Contact the manufacturer for the name of the nearest Representative/Distributor and pricing information.

WARRANTY

A limited twelve (12) month Material Replacement Warranty is available. For complete details contact Gemite’s Head Office.

TECHNICAL SERVICE

For advice on suitability of *Graffiti-Shield ST WB Cleaner* for specific project, Specification assistance and application advice, contact Technical Service: USA 888-443-6483 or Canada 905-672-2020.

Short Specification

The graffiti cleaner will be *Graffiti-Shield ST WB Cleaner* manufactured by Gemite Products Inc., [USA 888-443-6484] [Canada 905-672-2020]. It will meet all the Technical Data in the current *Graffiti-Shield ST WB Cleaner* Product Data Sheet.

Gemite Products Inc.
January 2018

9

1099623 Graffiti Resistant Coatings
1099635 Chemical Resistant Coatings