



MasterFormat: 09 96 23



GRAFFITI-SHIELD™ CLEANER

Graffiti Cleaner

DESCRIPTION

GRAFFITI-SHIELD CLEANER is an oil-emulsified organic cleaner used to remove graffiti. After approximately 30-40 cleanings, the original GRAFFITI-SHIELD film will be diminished and the surface needs to be recoated with GRAFFITI-SHIELD RECOAT.

USES

GRAFFITI-SHIELD CLEANER is used in removal of graffiti from wall surfaces previously protected with GRAFFITI-SHIELD protective coating.

FEATURES/BENEFITS

- Easy to use
- Highly active
- Cost-effective
- Spray, roller, or brush applied

PACKAGING

20 L (5.3 Gal.) Pails

COVERAGE

Coverage rate will vary according to the age, number of layers of graffiti, and type of graffiti coating being removed. Always conduct a test patch to determine suitability and usage level specific to the graffiti being removed.

SHELF LIFE

Shelf life is 12 months when stored in unopened containers on pallets in a cool, dry area.

SPECIFICATIONS/STANDARDS

- Complies with Canadian VOC Concentration Limits for Consumer Product Regulations.

APPLICATION

Application Method ... To remove graffiti from surfaces treated with GRAFFITI-SHIELD, apply GRAFFITI-SHIELD CLEANER by spraying, rolling, or brushing.

Spraying is preferable, particularly on rough surfaces.

Let GRAFFITI-SHIELD CLEANER act on the graffiti for 10 - 15 minutes and then wash with 14 - 17 MPa (2000 - 2500 psi) pressure water.

On rough surfaces that may "lock in" the graffiti or some graffiti sprays, the removal may not be complete and the procedure may have to be repeated.

After approximately 30 - 40 graffiti removals, the surface will require re-application of GRAFFITI-SHIELD.

Drying Time ... GRAFFITI-SHIELD dries to a wet edge in 30 minutes. It dries to the touch in one hour. The product achieves full cure in two days at 20° C.

Clean Up ... All tools and equipment should be cleaned with water immediately after use. Dried film can be removed by acetone.

PRECAUTIONS

Do not apply GRAFFITI-SHIELD when air temperature or surface temperature are or likely to be lower than 5° C or when rain is imminent. Highly porous surfaces with bug holes and roughness will allow the graffiti materials to "lock" in the surface crevices and make cleaning much more difficult. Some graffiti may remain on rough surfaces, even after cleaning.

W. R. MEADOWS, INC.

P.O. Box 338 • Hampshire, IL 60140-0338
Phone: 847/214-2100 • Fax: 847/683-4544
1-800-342-5976

www.wrmeadows.com • info@wrmeadows.com

HAMPSHIRE, IL / CARTERSVILLE, GA / YORK, PA
FORT WORTH, TX / BENICIA, CA / POMONA, CA
GOODYEAR, AZ / MILTON, ON / SHERWOOD PARK, AB



LIMITED WARRANTY

W. R. MEADOWS, INC. warrants at the time and place we make shipment, our material will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. Read complete warranty. Copy furnished upon request.

Disclaimer

The information contained herein is included for illustrative purposes only, and to the best of our knowledge, is accurate and reliable. W. R. MEADOWS, INC. cannot however under any circumstances make any guarantee of results or assume any obligation or liability in connection with the use of this information. As W. R. MEADOWS, INC. has no control over the use to which others may put its product, it is recommended that the products be tested to determine if suitable for specific application and/or our information is valid in a particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each product. Specifier and user shall determine the suitability of products for specific application and assume all responsibilities in connection therewith.